



THE LUXURY OF PROFESSIONAL RESULTS



MADE IN USA


speedqueen.com.au

 **Speed Queen®**

TOP LOAD WASHER & DRYER



AWNA62 BLACK



ADE3TR / ADG3TR BLACK




- 8.5 kg
- Fast 37 min normal wash cycle
- 210 deg agitation at 68 stokes per minute provide a superior washing result
- Heavy-duty, all metal Eversmooth transmission has only six moving parts for long lasting, durable performance
- Stainless Steel inner and Porcelain Steel outer bowl (Lifetime parts warranty against rust and corrosion)
- Programs include: Normal, Permanent Press and Delicate
- Additional options include: High Efficiency, Rinse & Spin and Spin only
- 10 Amp power required (Standard power point)

- 9 kg
- Performance vented drying (35-45 min, load type and model dependent)
- Whisper quiet, superior airflow of 85 litres per second results in faster drying with less wear and creasing of clothes
- Three temperature settings and auto dry feature ensure the dryer does not over dry items, therefore saving time, energy and money
- Choice between: Time dry, Automatic dry, Permanent press and Automatic dry Delicate
- Quick Dry: 20 Amp / Super Quick Dry: Nat/LP Gas

TOP LOAD WASHER & DRYER



AWNE92 BLACK



ADEE9R / ADGE9R BLACK



- 8.5 kg
- Fast 37 min normal wash cycle, with a quick wash of 33 min
- 210 deg agitation at 68 stokes per minute provide a superior washing result
- Heavy-duty, all metal Eversmooth transmission has only six moving parts for long lasting, durable performance
- Stainless Steel inner and Porcelain Steel outer bowl (Lifetime parts warranty against rust and corrosion)
- Programs include: Heavy Duty, Whites, Eco, Bulky, Delicates and Favourites
- Additional options include: Pre Wash, Extra Rinse, Soak and Delay Start
- 10 Amp power required (Standard power point)

- 9 kg
- Performance vented drying (35-45 min, load type and model dependent)
- Whisper quiet, superior airflow of 85 litres per second results in faster drying with less wear and creasing of clothes
- Four temperature settings and auto-sensing feature ensure the dryer does not over dry items, therefore saving time, energy and money
- 8 Drying cycles, favourite options, dryness and temperature selection, additional features such as Anti-wrinkle, Eco Dry and Signal finish
- Quick Dry: 20 Amp / Super Quick Dry: Nat/LP Gas



TRUSTED, RELIABLE, DURABLE, QUICK

As the world's largest laundry specialist for over a century, at Speed Queen quality comes first. We don't compromise on components or cut corners in design and engineering.

We plan, we test, and we build our machines with commercial grade metal parts that are tested to last up to 10,400 cycles, which could be 25 years' worth of laundry in your home, so you know you're getting the quality, durable product, generations of people have come to know and love.

Locally connected - We have offices in Sydney, Melbourne, Brisbane and Perth with a network of over a 1000 sales and service partners nationally. If you require any further information on our Speed Queen range please visit www.speedqueen.com.au or call **1300washer (1300 927 437)**.

FRONT LOAD WASHER & DRYER



AFNE9BSS PLATINUM



ADEE9BSS / ADGE9BSS PLATINUM



- 10 kg
- Stainless Steel inner and outer bowl
- Maximum spin speed 1,200 rpm
- Door opens 180° for easy loading and unloading
- 440 G-force extraction: removes more moisture and minimizes drying times and utility costs
- Programs Include: Heavy Duty, Whites, Bulky, Delicates and Favourites
- Additional options include: Pre Wash, Extra Rinse, Soak and Delay Start
- Extra rinse mode / 10 Preset cycles / Quick wash cycle just 24 minutes
- 4 Spin speeds / 4 Soil levels / 4 Water temperatures
- 4 Compartment dispenser

- 9 kg
- Performance Vented Drying (35-90 min load type and model dependent)
- Large, easy-to-clean lint compartment
- Largest door opening in the industry for easy loading and unloading with a Stainless Steel Drum
- Internal light and Reversible door hinge
- 8 Drying cycles
- 4 Drying temperature modes and 4 dryness modes
- Anti-wrinkle and Eco Dry modes
- Quick Dry: 20 Amp / Super Quick Dry: Nat/LP Gas



FRONT LOAD WASHER & DRYER

AFNE9B BLACK




ADEE8B / ADGE8B BLACK




- 10 kg
- Stainless Steel inner and outer bowl
- Maximum spin speed 1,200 rpm
- Door opens 180° for easy loading and unloading
- 440 G-force extraction: removes more moisture and minimises drying times and utility costs
- Programs Include: Heavy Duty, Whites, Bulky, Delicates and Favourites
- Additional options include: Pre Wash, Extra Rinse, Soak and Delay Start
- Extra rinse mode / 10 Preset cycles / Quick wash cycle just 24 minutes
- 4 Spin speeds / 4 Soil levels / 4 Water temperatures
- 4 Compartment dispenser

- 9 kg
- Performance vented drying (35-90 min load type and model dependent)
- Whisper quiet, superior airflow of 85 litres per second results in faster drying with less wear, and creasing of clothes
- Three temperature settings and auto dry feature ensure the dryer does not over dry items, therefore saving time, energy and money
- Galvanised Drum. Three-coat, commercial grade steel cabinet will look good for years to come
- 6 Drying cycles, dryness, temperature selection and signal finish
- Quick Dry: 20 Amp / Super Quick Dry: Nat/LP Gas





STACKED WASHER & DRYER



ATEE9A / ATGE9A BLACK

When space is at a premium, Speed Queen stack washer/dryers offer the perfect solution. This convenient design allows double the capacity in the space of one machine while sacrificing nothing in performance and wash/dry quality. Designed for ultimate user convenience, this two-in-one space saver with convenient located controls makes for easy access and operation.



- 10 kg
- Stainless Steel inner and outer bowl / Maximum spin speed 1,200 rpm
- Door opens 180° for easy loading and unloading
- 440 G-force extraction: removes more moisture and minimizes drying times and utility costs
- Programs Include: Heavy Duty, Whites, Bulky, Delicates and Favourites
- Additional options include: Pre Wash, Extra Rinse, Soak and Delay Start
- Extra rinse mode / 10 Preset cycles / Quick wash cycle just 24 minutes
- 4 Spin speeds / 4 Soil levels / 4 Water temperatures
- 4 Compartment dispenser

- 9 kg
- Performance vented drying (35-90 min load type and model dependent)
- Large, easy-to-clean lint compartment
- Largest door opening in the industry for easy loading and unloading with a colour bonded Galvanised Drum
- 8 Drying cycles and an internal light
- 4 Drying temperature modes and 4 dryness modes
- Anti-wrinkle and Eco Dry modes
- Quick Dry: 20 Amp / Super Quick Dry: Nat/LP Gas


TECHNICAL SPECIFICATIONS CALL 1300WASHER (1300 927 437) FOR MORE INFORMATION

SPEED QUEEN WASHING MACHINES - HOME RANGE		
MODEL NUMBER	TOP LOAD - TRADITIONAL AWWNA62 TOP LOAD - TOUCH AWWNE92	FRONT LOAD - AFNE9B / AFNE9BSS STACK - ATEE9A - ELECTRIC / ATGE9A - GAS
Wash Capacity	8.5 kg	10 kg
Dimensions (H X W X D)	1092 X 651 X 711mm	1027 X 683 X 796mm / Stack - 1986 X 683 X 796mm (including door)
Operating Clearances Required	Rear 80mm	Side 38mm / Rear 80mm / Stack requires 150mm top clearance
Shipping Dimensions (H X W X D)	1156 X 700 X 780mm	1156 X 732 X 832mm / Stack - 2032 X 760 X 860mm
Shipping Weight	89 kg	Front Load - 122 kg / Stack - 193 kg
Spin Speed (RPM)	710 / 473 rpm	1200 / 800 / 400 rpm / No Spin
Motor Size - Watts	375 W	750 W (Variable Speed)
WELS Rating / Water Consumption	3 Star / 117 L	3 Star / 126 L
Water Temperature Selection	AWNA62 - 3 / AWWNE92 - 4	4
Wash Bowl	Stainless	Stainless
Outer Wash Bowl	Porcelain Steel	Stainless
Electrical Requirements	240 V / 50 HZ AC / Single Phase	240 V / 50 HZ AC / Single Phase
Operating Water Pressure Required	138 - 830 KPA	138 - 830 KPA
Drain hose connection heights Min - Max	610 - 914mm Upstand	610 - 914mm Upstand
Drain hose diameter*	40mm	40mm
Automatic Balancing System	Yes	Yes

*Washing machine drain hose cannot be connected to any drainage system smaller than 30mm. NB - Please take note of operating clearances above.


SPEED QUEEN DRYERS - HOME RANGE		
MODEL NUMBER	ADE3TR-20AMP / ADEE9R-20AMP - ELECTRIC ADG3TR / ADGE9R - GAS: NAT / LP	TOUCH / PLATINUM / STACK ADEE8B / ADEE9B / ATEE9A - ELECTRIC ADGE8B / ADGE9B / ATGE9A - GAS: NAT / LP
Dryer Controls	Rear Control	Front Control
Drying Capacity	9 kg	9 kg
Dimensions (H X W X D) With leveling legs turned in to base	1092 X 683 X 711mm	1027 X 683 X 711mm / Stack - 1986 X 683 X 704mm
Shipping Dimensions (H X W X D)	1156 X 737 X 832mm	1156 X 760 X 860mm / Stack - 2032 X 760 X 860mm
Shipping Weight	65 kg	Single Dryer - 73 kg / Stack - 193 kg
Dryer Type*	Vented Dryer	Vented Dryer
Exhaust Vent Size	102mm	102mm
Venting exhaust direction Options - (May incur additional charges)	Electric - rear, left, right & down / Gas - rear, right & down	Electric - rear, left, right & down / Gas - rear, right & down
Operating Clearances	30mm side & 50mm rear	30mm side & 50mm rear
Venting exhaust direction Options - STACK (May incur additional charges)	-	Electric - rear, left & right / Gas - rear & right
Dryer door Width	525mm	525mm
Dryer door Hinge	Reversible	Reversible (excluding Stack models)
Heating Type	Electric or Gas	Electric or Gas
Electrical Requirements	240 V / 50 HZ AC / Single Phase	240 V / 50 HZ AC / Single Phase
Dryer breaker size	20 AMP - Electric / 10 AMP - Gas	20 AMP - Electric / 10 AMP - Gas
Heating Element**	20 AMP - 4,000 W	20 AMP - 4,000 W
Gas Consumption MJ***	21.9 MJ - Gas	21.9 MJ - Gas
Gas Inlet Connection***	3/8 NPT	3/8 NPT
Australian Gas Approval**	Yes	Yes
Shoe Dryer Rack - Part # 512082	Optional	Optional

KEY *All Speed Queen dryers need to be vented to atmosphere (vented outside), please contact 1300 927 437 for venting solutions. **Electric Models. ***Gas Models Only. ****Max ducting length 19.8mtr, reducing by 3mtrs for each 90deg bend. ****Any dryer should have sufficient clearance around it for needed ventilation and for the ease of installation and servicing. Minimum 30mm side & 50mm rear clearance.




NB: Minimum clearance is 10mm side & 80mm rear clearance

REAR CONTROL DRYER BLACK




NB: Minimum clearance is 30mm sides & 50mm rear clearance (excludes ducting)

FRONT LOAD BLACK



NB: Minimum clearance is 38mm side & 80mm rear clearance

FRONT CONTROL DRYER BLACK



NB: Minimum clearance is 30mm sides & 50mm rear clearance (excludes ducting)

